











Item number		Article description
CLAMP-5AC		AC current clamp, 5A ACrms, 10 kHz bandwidth
CLAMP-20AC		AC current clamp, 20A ACrms, 10 kHz bandwidth
CLAMP-200AC		AC current clamp, 200A ACrms, 10 kHz bandwidth
CLAMP-1000AC		AC current clamp, 1000A ACrms, 10 kHz bandwidth
FLEX-Mini-300		AC Rogowski coil, 17 cm loop length, 4.5 cm loop diameter, 3m connection cable
FLEX-Mini-300-25		AC Rogowski coil, Ranges:30A, 300A, 3000A, 30kA; 25 cm length, 7 cm diameter, 3m connection cable
FLEX-Mini-300-35		AC Rogowski coil, Ranges:30A, 300A, 3000A, 30kA; 35 cm length, 10 cm diameter, 3m connection cable
FLEX-3000		AC Rogowski coil, 45cm loop length, 12.5 cm loop diameter, 3m connection cable
FLEX-6000		AC Rogowski coil, 80 cm loop length, 25 cm loop diameter, 3m connection cable
FLEX-10k		AC Rogowski coil, 120 cm loop length, 3m connection cable
LEM-ATO		LEM ATO current sensor 32A or 50A or 75A or 100A or 125A with 1m connection cable and ODO connector
CLAMP-300DC		AC/DC current clamp, 150A DC or ACrms, DC to 100 kHz bandwidth
CLAMP-300DCS		AC/DC current clamp, 150A DC or ACrms, DC to 100 kHz bandwidth
CLAMP-2000DC		AC/DC current clamp, 1800A DC or ACpeak, DC to 20 kHz bandwidth

Item number	Article description	
ICS-10A		Direct current input module Hall sensor based 10A, bandwidth 150kHz, measuring range: 100mA to 10A, CAT II 1000V, current path connection via banana socket
IPCS-10A		Direct current input module zero sequence transformer based 10A, bandwidth 500kHz, measuring range 10mA - 10A, CAT II 300V, current path connection via banana jack
IPCS-25A		Direct current input module zero sequence transformer based, bandwidth 500kHz, measuring range 10mA - 25A, CAT II 300V, current path connection via banana jack
IPCS-50A		Direct current input module zero sequence transformer based, bandwidth 500kHz, measuring range 10mA - 50A, CAT II 300V, current path connection via screw terminal
Adapter ODU-BNC	Adapter cable from ODU (current clamp input) to BNC, length 30cm	
Adapter ODU-BAN		Adapter cable from ODU (current clamp input) to 4mm banana, length 30cm
Adapter ODU-DSUB		Adapter cable from ODU (current clamp input) to DSUB (announcement pinning required), length 30cm
Adapter ODU-Amph		Adapter cable from ODU (current clamp input) to Amphenol (PNA560, PNA571), length 30cm
Adapter ODU-open end		Adapter cable from ODU to Open-End
Rogo Extender	Extension cable for Rogowski coils (ODU male to ODU female), length 3m	
Safety test lead CAT IV - 2.5		Safety measuring cable CAT III 1000V / CAT IV 600V, with integrated fuse (0,5A), max. load 20A , cross section 2,5mm <sup>2</sup> / length 2m / price per piece
Safety test lead CAT IV - 1.5		Safety measuring cable CAT III 1000V / CAT IV 600V, with integrated fuse (0,5A), max. load 25A , cross section 1,5mm <sup>2</sup> / length 2m / price per piece
Further sensors on request	Any other current sensors (iron core clamps, Rogowski coils, AC/DC Hall-compensated current clamps, zero flow transformers, direct current inputs) can be connected directly to the device and supplied by the device	