

SINEAX® CAM, programmable, MODBUS interface, USB

Basic device CAM		Input frequency range		Power supply		I/O module 1 (clamps 41-44)	I/O module 2 (clamps 51-54)	I/O module 3 (clamps 61-64)	I/O module 4 (clamps 71-74)	Test protocol	Option Logger	Option Lists	Bus connection		
Without display	With display	45...60...65 Hz	10...50/60...70 Hz	Hn: 100...230V AC/DC	Hn: 24...60V DC	2 analog outputs bipolar +/- 20mA	2 analog outputs bipolar +/- 20mA	2 analog outputs bipolar +/- 20mA	2 analog outputs bipolar +/- 20mA	Test certificate English	Without Logger	Without alarm, event, operator list	Without Bus interface	Ethernet, Modbus/TCP protocol	
•	-	•	-	•	-	•	•	•	•	•	•	•	•	-	CAM-1115 555E 000
•	-	•	-	-	•	•	•	•	•	•	•	•	•	-	CAM-1125 555E 000
•	-	•	-	•	-	•	•	•	•	•	•	•	-	•	CAM-1115 555E 001
•	-	•	-	-	•	•	•	•	•	•	•	•	-	•	CAM-1125 555E 001
•	-	-	•	•	-	•	•	•	•	•	•	•	•	-	CAM-1215 555E 000
•	-	-	•	-	•	•	•	•	•	•	•	•	•	-	CAM-1225 555E 000
•	-	-	•	•	-	•	•	•	•	•	•	•	-	•	CAM-1215 555E 001
•	-	-	•	-	•	•	•	•	•	•	•	•	-	•	CAM-1225 555E 001