

LINAX® PQ5000, Multifunctional Power Quality Analyzer, Class A

Basic device		Input frequency range	Power supply		Bus interface	Standard protocol	Standard I/Os		Uninterruptible power supply		Extension 1						Type code	Extention 3 (Extra feature)	Article number		
Without display, for top-hat rail mounting	With TFT display, for instrument panel mounting	4 current inputs, 42...50/60...69.5Hz	Rogowski inputs, 50/60 Hz	Nominal voltage 100...230 V AC/DC	Nominal voltage 24...48 V DC	Ethernet (TCP/IP) + RS485 (RTU)	REST Interface + Modbus	1 digital input passive	2 digital outputs passive	Without UPS	With UPS	Without extension 1	4 analog outputs +/-20mA	Profinet interface	IEC61850 interface	Temperature monitoring, 2 channels	PME central unit	IRIG-B connection module		Without Extension 2	Test certificate English
•	-	•	-	•	-	•	•	•	•	•	-	•	-	-	-	-	-	•		•	193057
•	-	-	•	•	-	•	•	•	•	•	-	-	-	-	-	•	-	•		•	193065
-	•	•	-	•	-	•	•	•	•	•	-	•	-	-	-	-	-	•		•	193073
-	•	-	•	•	-	•	•	•	•	•	-	•	-	-	-	-	-	•		•	193081
-	•	•	-	•	-	•	•	•	•	-	•	-	-	-	-	-	-	•		•	193089
-	•	•	-	•	-	•	•	•	•	•	-	-	-	•	-	-	-	•		•	193097
-	•	•	-	•	-	•	•	•	•	•	-	-	•	-	-	-	-	•		•	193105